

3 – WAY FULLBORE BALL VALVE, STAINLESS STEEL

PN63




3-way fullbore ball valve, with L- and T-port in stainless steel.

Working pressure:

1/4" – 2" : 63 bar



NR	PART NAME	MATERIAL
1	Body	1.4408
2	End Caps	1.4408
3	Seat	P.T.F.E
4	Ball	CF8M
5	Stem	AISI 316
6	End seals	P.T.F.E
7	Thrust washer	P.T.F.E
8	Gland	AISI 304
9	Handle	AISI 304
10	Handle washer	AISI 304
11	Washer	AISI 304
12	Handle nut	AISI 304
13	Handle cover	PVC
14	End cap	CF8M
15	Stem packing	P.T.F.E
16	End packings	P.T.F.E
17	Gland washer	AISI 304
18	Bolts	AISI 304



DIM	ART. NR. BSP – L-port	ART. NR. BSP – T-port	ØD mm	L mm	E mm	B mm	D mm	C mm	A mm	F mm	W mm	H mm	M mm	N mm	N-M mm	WEIGHT kg
1"			20	101	35,4	9,5	10,7	15	17	50	180	90	50	M6	196	1,67
1 1/4"			25	119	35,4	9,5	10,7	15	17	59	180	95	50	M6	266	2,35
1 1/2"			32	130	49,5	8,0	14	20	19	62	232	101	70	M8	363	3,7
2"			38	148,5	49,5	8,0	14	20	19	72	232	109	70	M8	500	5,69