

GATE VALVE CR

CIM 70/BS – CR - PN 20


Typical application: Gate valve for usage on non-aggressive mediums.

Pressure class:

1/4" – 4" : 20 bar.



PART NAME	MATERIAL
Body	Brass EN 12165 CW 602N
Topcover	Brass EN 12165 CW 602N
Spindle	Brass EN 12165 CW 602N
Innerparts	Brass EN 12165 CW 602N
Spindlering	Brass EN 12165 CW 602N
Topcover Seal	Novus Supra
Bonnet Nut	Brass EN 12165 CW 602N
Bonnet seal	P.T.F.E.
Bonnet Ring	Brass EN 12165 CW 602N
Locking Nut	8.8 FZB
Wheel	AluminiumN SI 12



DIM	ART. NR.	A mm	B mm	C mm	D mm	CH1 mm	CH2 mm	CH3 mm	D mm	TORQUE NM	WEIGHT kg
1/4"	5504205	50	71	40	11,0	23	20	17	7	12	0,16
3/8"	5504209	50	71	40	11,0	23	20	17	7	12	0,16
1/2"	5504214	56	80	54	16,0	27	22	19	8	13	0,27
3/4"	5504219	60	97	59,0	16,3	32,5	24,0	21,0	8	19	0,41
1"	5504224	65	108	66	19,1	40,0	26,0	21,0	9	25	0,54
1 1/4"	5504229	78	121,5	74,0	21,4	48,8	32,0	25,0	10	32	0,82
1 1/2"	5504234	80	142	76,0	21,4	55,5	42,0	25,0	11	39	1,13
2"	5504239	93	165	86	25,7	68,5	52	29	12	51	1,83
2 1/2"	5504244	120	210	92	23	85,00	60	30	16	64	3,42
3"	5504249	140	247	98	25	101	80	37	17	77	5,15
4"	5504254	175	290	106	25	132	110	45	19	102	8,78