



GATEVALVE

CIM 72F – PN 16

Heating plants, sanitary systems, plumbing services, gasoline networks, pneumatic systems and low pressure steam (7 bar/1700C).



PART NAME	MATERIAL
Body	Bronze UNI 7013 – 8° – ISO 1338
Topcover	Brass EN 12165 CW 617N
Spindle	Brass EN 12164 CW 614N
Spindlering	Brass EN 12164 CW 614N
Topcover Seal	NA 1030 Gr.
Bonnet Nut	Brass EN 12164 CW 614N
Bonnet seal	AF 15/MA
Bonnet Ring	Brass EN 12164 CW 614N
Locking Nut	EL Zink
Wheel	Aluminium SI 12



DN	A mm	FL. BOR	B mm	ARB. TR.	C mm	D mm	E mm	CH1 mm	CH2 mm	D mm	WEIGHT kg
20	60	16	95	16	83,0	105,0	8,0	30,0	18,0	8,0	1,65
25	65	16	102	16	89	120,0	10,0	32,0	18,0	8,0	2,45
32	75	16	120	16	98,0	140,0	10,0	32,0	21,0	10,0	3,17
40	80	16	134	16	115,0	150,0	11,0	39,0	23,0	10,0	4,17
50	90	16	180	16	128	162	11	47	25	12	5,11
65	90	16	173	16	141	175	12	49	25	12	7,69

EN 10204 – 3.1 certificate available