

OVENTROP HYDROCONTROL VGC BALANCING VALVE

Typical application: For balancing of various heating, cooling and hot water systems. DNV Type approval certificate for shipsbuilding.

Temp. range:


-10 / +150°C

Max pressure:

16 bar / PN16



PART NAME	MATERIAL
Connection	Groove connection, Victaulic, Grinnell or similar
Valve body	Cast iron with external corrosion protection 120µ
Bonnet, stem, disc	Bronze, Brass resistant to de-zincification
Valve	Siliconfri as standard version
Seal	PTFE
Sealing	Double O-ring seal for spindle



DN	NRF NR.	L mm	D EN10226	T mm	L mm	H mm	PRESSURE RATING
65/ 76,1	311064051	290	76,1	188	110	9,1	PN 16
80/ 88,9	311063052	310	88,9	203	110	12,7	PN 16
100/ 114,3	311063053	350	114,3	240	160	20,6	PN 16
125/ 139,7	311064054	400	139,7	283	160	31,9	PN 16
150/ 168,3	311063055	480	168,3	285	160	43,5	PN 16
200/ 219,1	311063056	600	219,1	467	300	116	PN 16
250/ 273	311063057	730	273	480	300	171,5	PN 16
300/ 323,9	311063058	850	323,9	515	300	236,5	PN 16