

OVENTROP HYDROCONTROL VTR BALANCING VALVE

Typical application: For balancing of various heating, cooling and hot water systems. DNV Type approval certificate for shipsbuilding.

Temp. range:


-20 / +150°C

Max pressure:

25 bar / PN25



PART NAME	MATERIAL
Connection	Female thread
Valve body and bonnet	Bronze, Rg 5
Spindle	Brass resistant to de-zincification
Cone	Brass resistant to de-zincification
Valve	Silicone free as standard version
Seal	PTFE
Sealing	Double O-ring seal for spindle



DN	NRF NR.	ART. NR.	L mm	D mm	H mm	D mm	WEIGHT kg	PRESSURE RATING
10	8521067	311060203	Rp 3/8"	10,1	73	114	0,73	PN 25
15	8521068	311060204	Rp 1/2"	13,2	80	114	0,73	PN 25
20	8521069	311060206	Rp 3/4"	14,5	84	116	0,78	PN 25
25	8521071	311060208	Rp 1"	16,8	97,5	119	1,09	PN 25
32	8521072	311060210	Rp 1 1/4"	19,1	110	136	1,46	PN 25
40	8521073	311060212	Rp 1 1/2"	19,1	120	138	1,81	PN 25
50	8521074	311060216	Rp 2"	25,7	150	148	2,74	PN 25