


STEEL BLINDFLANGE, PN 10, 16 & 40

Material P245GH/P250GH/ C22.8

EN 1092-1 Type05 Flat Face (DIN 2527)

EN 10204-3.1 certifikate



PN 10 – NS 2545

DN	D mm	B mm	ØK mm	NO OF BOLTS	BOLT	D2 mm	WEIGHT kg	ART. NR
200	340	24	295	8	M20	22	16,4	1257879
250	395	26	350	12	M20	22	24,0	1257889
300	445	26	400	12	M20	22	30,9	1257894
350	505	26	460	16	M20	22	39,6	1257899
400	565	26	515	16	M24	26	49,5	1257909
450	615	28	565	20	M24	26	63,0	1257914
500	670	28	620	20	M24	26	75,0	1257919
600	780	34	725	20	M27	309	124	1257929

PN 16 – NS 2546

DN	D mm	B mm	ØK mm	NO OF BOLTS	BOLT	D2 mm	WEIGHT kg	ART. NR
15	95	14	65	4	M12	14	0,72	1258119
20	105	16	75	4	M12	14	0,95	1258124
25	115	16	85	4	M12	14	1,24	1258129
32	140	16	100	4	M16	18	1,80	1258134
40	150	16	110	4	M16	18	2,05	1258139
50	165	18	125	4	M16	18	2,88	1258144
65	185	18	145	8	M16	18	3,50	1258149
80	200	20	160	8	M16	18	4,70	1258154
100	220	20	180	8	M16	18	5,62	1258159
125	250	22	210	8	M16	18	8,15	1258164
150	285	22	240	8	M20	22	10,5	1258169
200	340	24	295	12	M20	22	16,00	1258179
250	405	26	355	12	M24	26	25,60	1258189
300	460	28	410	12	M24	26	35,00	1258194

PN 40 – NS 2547

DN	D mm	B mm	ØK mm	NO OF BOLTS	BOLT	D2 mm	WEIGHT kg	ART. NR
15	95	16	65	4	M12	14	0,82	1258719
20	105	18	75	4	M12	14	1,12	1258724
25	115	18	85	4	M12	14	1,37	1258729
32	140	18	100	4	M16	18	2,05	1258734
40	150	18	110	4	M16	18	2,35	1258739
50	165	20	125	4	M16	18	3,25	1258744
65	185	22	145	8	M16	18	4,29	1258749
80	200	24	160	8	M16	18	5,55	1258754
100	235	24	190	8	M20	22	7,60	1258759
125	270	26	220	8	M24	26	10,7	1258764
150	300	28	250	8	M24	26	14,45	1258769
200	375	36	320	12	M27	30	28,7	1258779
250	450	38	385	12	M30	33	44,5	1258789

Information and technical data are given as guidance only