

SWING CHECK VALVE – PN 10/16



Valve for installation between flanges.

Suitable for horizontal & vertical installation.

Available with O-ring in EPDM & PTFE and with spring.



PART	MATERIAL	
	BRONZE VERSION	STAINLESS STEEL VERSION
Body	Rg5 (CuSn5ZnPb 5-C)	AISI 316
Disc	Rg5 (CuSn5ZnPb 5-C)	AISI 316
Seals	NBR	NBR



DN	BRONZE VERSION ART. NR.	AISI 316 VERSION ART. NR.	ØD mm	ØC mm	L mm	WEIGHT kg	PRESSURE RATING TEMP 100°C
40	041107	041077	94	22	16	0,8	PN 16
50	041108	041078	109	30	16	1,1	PN 16
65	041109	041079	129	37	16	1,6	PN 16
80	041110	041080	144	48	16	2	PN 16
100	041111	041081	164	70	16	2,4	PN 16
125	041112	041082	194	95	18	3,3	PN 16
150	041113	041083	220	121	19	4,5	PN 16
200	041114	041084	275	155	29	10	PN 10
250	041115	041085	330	196	29	16	PN 10
300	041116	041086	380	230	38	28	PN 10
350	041117		440	250	41	35	PN 10
400	041118		491	303	51	60	PN 10
450	041119		541	358	51	68	PN 10
500	041120		596	398	61	80	PN 10
600	041221		698	480	71	120	PN 10