

## KOBBER-NIKKEL 90/10 RØR

CuNi 90/10

DIN 86019

Material sertifikat EN 10204/3.1



| OD    | S mm | LENGDER | ART. NR. |
|-------|------|---------|----------|
| 16,0  | 1,5  | 0,63    | 5017512  |
| 20,0  | 1,5  | 0,80    | 5017523  |
| 20,0  | 2,0  | 1,06    | 5017527  |
| 22,0  | 1,5  | 0,86    | 1912215  |
| 25,0  | 1,5  | 0,99    | 5017536  |
| 25,0  | 2,0  | 1,32    | 5017541  |
| 28,0  | 1,5  | 1,11    | 1912815  |
| 30,0  | 1,5  | 1,19    | 5017549  |
| 30,0  | 2,0  | 1,56    | 5017554  |
| 35,0  | 1,5  | 1,37    | 1913515  |
| 38,0  | 1,5  | 1,53    | 5017563  |
| 38,0  | 2,0  | 2,01    | 5017567  |
| 42,0  | 1,5  | 1,68    | 1914215  |
| 44,5  | 1,5  | 1,80    | 5017572  |
| 44,5  | 2,0  | 2,38    | 5017576  |
| 54,0  | 1,5  | 2,20    | 1915415  |
| 57,0  | 1,5  | 2,33    | 5017585  |
| 57,0  | 2,0  | 3,07    | 5017589  |
| 76,0  | 2,0  | 4,14    | 5017598  |
| 76,0  | 2,5  | 5,14    | 5017603  |
| 89,0  | 2,0  | 4,86    | 5017607  |
| 89,0  | 2,5  | 6,04    | 5017612  |
| 108,0 | 2,5  | 7,37    | 5017616  |
| 133,0 | 2,5  | 9,12    | 5017621  |
| 133,0 | 3,0  | 10,90   | 5017625  |
| 159,0 | 2,5  | 10,93   | 5017629  |
| 159,0 | 3,0  | 13,08   | 5017634  |
| 219,0 | 3,0  | 18,11   | 5017643  |
| 267,0 | 3,0  | 22,13   | 5017652  |
| 324,0 | 4,0  | 35,77   | 5017665  |
| 368,0 | 4,0  | 40,69   | 5017672  |
| 419,0 | 4,0  | 46,39   |          |
| 457,0 | 4,0  | 50,91   |          |
| 508,0 | 4,5  | 63,63   |          |
| 610,0 | 5,0  | 84,96   |          |
| 711,0 | 6,0  | 118,80  |          |
| 813,0 | 6,0  | 135,99  |          |
| 914,0 | 8,0  | 203,57  |          |

