



KRAGEFLENS, PN 16, 25 & 40

Materiale P245GH – C22.8

EN 10204-3.1 sertifikat



PN 16 – EN 1092-1 TYPE 11/PN16 (DIN 2633)

DN	RØR D1	D4 mm	D mm	B mm	K mm	H1 mm	ANT. BOLTER	BOLT	D2 mm	VEKT kg	ART. NR.
15	21,3	45	95	14	65	35	4	M12	14	0,65	1252629
20	26,9	58	105	16	75	38	4	M12	14	0,95	1252639
25	33,7	68	115	16	85	38	4	M12	14	1,14	1252649
32	42,4	78	140	16	100	40	4	M16	18	1,69	1252659
40	48,3	88	150	16	110	42	4	M16	18	1,86	1252669
50	60,3	102	165	18	125	45	4	M16	18	2,53	1252679
65	76,1	122	185	18	145	45	4	M16	18	3,06	1252684
80	88,9	138	200	20	160	50	8	M16	18	3,70	1252689
100	114,3	158	220	20	180	52	8	M16	18	4,62	1252699
125	139,7	188	250	22	210	55	8	M16	18	6,30	1252709
150	168,3	212	285	22	240	55	8	M20	22	7,75	1252719
200	219,1	268	340	24	295	62	12	M20	22	11,00	1252729
250	273,0	320	405	26	355	70	12	M24	26	15,60	1252734
300	323,9	378	460	28	410	78	12	M24	26	22,00	1252744

PN 40 – EN 1092-1 TYPE 11/PN40 (DIN 2635)

DN	RØR D1	D4 mm	D mm	B mm	K mm	H1 mm	ANT. BOLTER	BOLT	D2 mm	VEKT kg	ART. NR.
15	21,3	45	95	16	65	38	4	M12	14	0,75	1253229
20	26,9	58	105	18	75	40	4	M12	14	1,06	1253239
25	33,7	68	115	18	85	40	4	M12	14	1,29	1253249
32	42,4	78	140	18	100	42	4	M16	18	1,88	1253259
40	48,3	88	150	18	110	45	4	M16	18	2,33	1253269
50	60,3	102	165	20	125	48	4	M16	18	2,82	1253279
65	76,1	122	185	22	145	52	8	M16	18	3,74	1253284
80	88,9	138	200	24	160	58	8	M16	18	4,75	1253289
100	114,3	162	235	24	190	65	8	M20	22	6,52	1253299
125	139,7	188	270	26	220	68	8	M24	26	9,07	1253309
150	168,3	218	300	28	250	75	8	M24	26	11,80	1253319

PN 25 – EN 1092-1 TYPE 11/PN25 (DIN 2634)

DN	RØR D1	D4 mm	D mm	B mm	K mm	H1 mm	ANT. BOLTER	BOLT	D2 mm	VEKT kg	ART. NR.
200	219,1	278	360	30	310	80	12	M24	26	17,00	1253029
250	273,0	335	425	32	370	88	12	M27	30	24,40	1253039
300	323,9	395	485	34	430	92	16	M27	30	31,20	1253044