

## SADELSTYKKER I KOBBER NIKKEL

Materiale CuNi 90/10

DIN 86087

Sertifikat EN 10204-3.1 tilgjengelig



| ØD mm | E mm | H mm | A mm | VEKT kg/m | ART. NR. |
|-------|------|------|------|-----------|----------|
| 25,0  | 1,5  | 22   | 40   | 0,06      |          |
| 30,0  | 1,5  | 30   | 50   | 0,10      |          |
| 30,0  | 2,0  | 30   | 50   | 0,19      | 5018329  |
| 38,0  | 1,5  | 35   | 64   | 0,11      | 5018334  |
| 38,0  | 2,0  | 35   | 64   | 0,19      | 5018338  |
| 44,5  | 1,5  | 35   | 74   | 0,15      | 5018343  |
| 44,5  | 2,0  | 35   | 74   | 0,20      | 5018347  |
| 57,0  | 1,5  | 40   | 97   | 0,25      | 5018352  |
| 57,0  | 2,0  | 40   | 97   | 0,35      | 5018356  |
| 76,1  | 2,0  | 50   | 126  | 0,48      | 5018365  |
| 76,1  | 2,5  | 50   | 126  | 0,58      | 5018369  |
| 88,9  | 2,0  | 55   | 149  | 0,76      | 5018374  |
| 88,9  | 2,5  | 55   | 149  | 0,95      | 5018378  |
| 108,0 | 2,5  | 75   | 188  | 1,30      | 5018383  |
| 133,0 | 2,5  | 85   | 233  | 1,70      | 5018392  |
| 133,0 | 3,0  | 85   | 233  | 2,04      | 5018396  |
| 159,0 | 2,5  | 95   | 279  | 2,60      | 5018401  |
| 159,0 | 3,0  | 95   | 279  | 3,12      | 5018405  |
| 219,1 | 3,0  | 125  | 379  | 5,70      | 5018409  |
| 219,1 | 4,0  | 125  | 379  | 6,65      | 5018414  |
| 267,0 | 3,0  | 155  | 447  | 8,70      | 5018421  |
| 267,0 | 4,0  | 155  | 447  | 11,60     | 5018423  |
| 323,9 | 4,0  | 185  | 560  | 13,00     | 5018432  |
| 368,0 | 4,0  | 200  | 613  | 12,35     | 5018434  |
| 419,0 | 4,0  | 225  | 680  | 17,35     |          |
| 457,0 | 4,0  | 250  | 800  | 21,70     |          |
| 508,0 | 4,5  | 275  | 880  | 28,80     |          |
| 610,0 | 5,0  | 300  | 1020 | 47,20     |          |

