



SLUSEVENTIL

CIM 72F – PN 16

Typisk bruksområde: Varmeanlegg, sanitærsystemer, olje og bensin bestandig, luft og lavtrykk damp (7 bar v/1700C).



DETALJ	MATERIALE
Hus	Bronse UNI 7013 – 8° – ISO 1338
Toppdeksel	Messing EN 12165 CW 617N
Spindel	Messing EN 12164 CW 614N
Spindelring	Messing EN 12164 CW 614N
Toppdeksel pakning	NA 1030 Gr.
Pakkboks mutter	Messing EN 12164 CW 614N
Pakkboks pakning	AF 15/MA
Pakkboks Ring	Messing EN 12164 CW 614N
Låsemutter	EL Zink
Ratt	Aluminium SI 12



DN	A mm	FL. BOR	B mm	ARB. TR.	C mm	D mm	E mm	CH1 mm	CH2 mm	D mm	VEKT kg
20	60	16	95	16	83,0	105,0	8,0	30,0	18,0	8,0	1,65
25	65	16	102	16	89	120,0	10,0	32,0	18,0	8,0	2,45
32	75	16	120	16	98,0	140,0	10,0	32,0	21,0	10,0	3,17
40	80	16	134	16	115,0	150,0	11,0	39,0	23,0	10,0	4,17
50	90	16	180	16	128	162	11	47	25	12	5,11
65	90	16	173	16	141	175	12	49	25	12	7,69

EN 10204 – 3.1 Sertifikat tilgjengelig